



MBI[®]



RP-IT

ROTATING PULVERIZER

REPARK

www.REPARK.it



RP-IT

ROTATING PULVERIZER



Due to its high versatility and efficacy, the RP-IT has become a benchmark in the demolition industry. It is suitable for both primary and secondary demolition, also on high reach applications. The interchangeable wear parts simplify maintenance and ensure a perfect fit with different jobs.

• The **reinforced RP-IT structure** is designed to last forever and facilitates the crushed material drop off increasing efficiency.

• The continuous **hydraulic rotation** enables precise positioning during in height demolitions and ground operations, while its robust components **grant high durability**.

• The **2 different jaw plate** available ensure a perfect fit with the specific job. The CRP plate, with a single tooth, grants higher penetration on tough concrete and is indicated for primary demolition. The PP plate, with double teeth, maximizes productivity and is mostly used for secondary demolition.

PLATE CRP



PLATE PP



• The interchangeable parts, like teeth plates and blades, ensure **quick and easy maintenance**.




RP10-IT
RP16-IT
RP20-IT
RP30-IT



RP40-IT
RP50-IT
RP80-IT

• The **Speed-Valve** reduces opening and closing time boosting productivity.



TECHNICAL DATA

BT.RP-IT.10

MODEL		RP10-IT	RP16-IT	RP20-IT	RP30-IT	RP40-IT	RP50-IT	RP80-IT
ROTATION		360° Hydraulic						
EXCAVATOR WEIGHT	t	10-15	16-20	21-26	27-35	35-50	50-65	70-95
TOOL WEIGHT *	kg	1100	1690	2000	2850	4100	5200	8200
OPENING	mm	580	700	750	900	1000	1100	1250
HEIGHT MAX.	mm	1710	2150	2130	2400	2780	3000	3600
HYDRAULIC WORKING PRESSURE	bar	300-350	300-350	300-350	300-350	300-350	300-350	300-350
OIL FLOW	l/min	100-180	130-150	180-200	200-220	220-280	335-375	500-600

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.
* Tool weight does include Mantovanibenne top bracket.

RIE: 978721ITE 12/16 REV.02

