



### Coolers Range

| Product Code   | Type of Setting                   | Overall H | Fan Ø | Fan Power m³/h | M.R. dm³ | Power Consumpt. |
|----------------|-----------------------------------|-----------|-------|----------------|----------|-----------------|
| RU0100630000   | UNCOVERED                         | 45        | -     | -              | 4,24     | -               |
| RU0100630011   | 12V Suct.                         | 210       | 305   | 1839           | 4,24     | 16,5 A          |
| RU0100630012   | 12V Blow.                         | 210       | 305   | 1736           | 4,24     | 14,9 A          |
| RU0100630021   | 24V Suct.                         | 210       | 305   | 2161           | 4,24     | 10,3 A          |
| RU0100630022   | 24V Blow.                         | 210       | 305   | 2050           | 4,24     | 9,1 A           |
| RU0100630031 * | 230V-50/60Hz Suct.                | 175       | 300   | 3745           | 4,24     | 1,55 A          |
| RU0100630032 * | 230V-50/60Hz Blow.                | 175       | 300   | 3745           | 4,24     | 1,55 A          |
| RU0100630041   | 230/400V-50/60Hz 3FN Suct.        | 175       | 300   | 3350           | 4,24     | 0,48 A          |
| RU0100630042   | 230/400V-50/60Hz 3FN Blow.        | 175       | 300   | 3350           | 4,24     | 0,48 A          |
| RU0100630051   | Pred. Hydraulic. Suct. (Supp. G2) | 228       | 300   | 3080           | 4,24     | 0,41 kW         |
| RU0100630052   | Pred. Hydraulic. Blow. (Supp. G2) | 225       | 300   | 3080           | 4,24     | 0,41 kW         |

\* In SINGLE PHASE models (\*31/\*32), ADJUSTABLE THERMOSTAT 0-90° on request

### Technical Specification

