



Coolers Range

| Product Code | Type of Setting | Overall H | Fan \varnothing | Fan Power m^3/h | M.R. dm^3 | Power Consumpt. |
|----------------|-----------------------------------|-----------|-------------------|-------------------|-------------|-----------------|
| RU0100610000 | UNCOVERED | 45 | - | - | 2,13 | - |
| RU0100610011 | 12V Suct. | 140 | 190 | 446 | 2,13 | 6,4 A |
| RU0100610012 | 12V Blow. | 140 | 190 | 497 | 2,13 | 6,4 A |
| RU0100610021 | 24V Suct. | 140 | 190 | 419 | 2,13 | 2,8 A |
| RU0100610022 | 24V Blow. | 140 | 190 | 505 | 2,13 | 3,3 A |
| RU0100610031 * | 230V-50/60Hz Suct. | 135 | 200 | 1025 | 2,13 | 0,34 A |
| RU0100610032 * | 230V-50/60Hz Blow. | 135 | 200 | 1025 | 2,13 | 0,34 A |
| RU0100610041 | 230/400V-50/60Hz 3FN Suct. | 135 | 200 | 1020 | 2,13 | 0,13 A |
| RU0100610042 | 230/400V-50/60Hz 3FN Blow. | 135 | 200 | 1020 | 2,13 | 0,13 A |
| RU0100610051 | Pred. Hydraulic. Suct. (Supp. G1) | 185 | 195 | 958 | 2,13 | 0,7 kW |
| RU0100610052 | Pred. Hydraulic. Blow. (Supp. G1) | 185 | 195 | 958 | 2,13 | 0,7 kW |

* In SINGLE PHASE models (*31/*32), ADJUSTABLE THERMOSTAT 0-90° on request

Technical Specification

