



ELECTRIC PUSH-PUSH CONTROL-12V (D3M)

| | |
|---------------------------|----------------|
| Rated voltage | 12 VDC |
| Rated current | 3 A |
| Rated power | 45 W |
| Permitted working voltage | +/-10% Nominal |
| Max ambient temperature | +40°C |
| Max oil temperature | +80°C |
| Operation time | S1 (100%) |
| Protection degree | IP65 |
| Insulation degree | H |
| Standard connector | DIN 43650 |

STANDARD WORKING CONDITION

| | |
|------------------------------|---|
| Max. Inlet Flow | 55 l/min |
| Max. Input Pressure | 350 bar |
| Max. back pr. on Tank line | 20 bar |
| Operating temperature range | -20/+80°C |
| Kinematic Viscosity Range | 10-300 cst |
| Max. Contamination level | 9 (NAS 1638) - 20/18/15 (ISO 4406:1999) |
| Recommended Filtration level | b10 >75 (ISO 16889 : 2008) |
| PORT DIMENSIONS: | |
| Tank Port T | 1/2"-BSP |
| Inlet Port P | 1/2"-BSP |
| Working Ports A & B | 1/2"-BSP |

Description: HC-D3M/8



| | | | |
|--------------|------------------|--------------|---------|
| Group: D3M | | Scale | |
| Approv. | Date | Schema Code | |
| | | 90286 | |
| Designer: MS | Date: 17/06/2014 | CODE: I06959 | Mod.: 0 |