

SCORPIUS N4403 QD

NORDIC LIGHTS® Scorpius N4403 QD work light offers strong illumination with an operational lumens output of 4200 lm. This LED work light is equipped with the revolutionizing QUAKE dampening system, taking protection against vibration and shock to a whole new level. The Scorpius N4403 QD is suitable for harsh conditions and a range of applications.



Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.

TECHNICAL DATA

Theoretical Lumens Output	4800 lm	Vibration	20Grms 24-2000Hz, 4.65Grms 12-2000Hz
Operational Lumens Output	3000 lm	Lens	PC
Colour Temperature	5700 K	Body / Housing	Aluminium
Nominal Voltage DC	12 - 24 V	Weight	1.6 kg
Input Voltage DC	9 - 32 V	IP Rating	IP68, IP6K9K, SAE J1455
Power Consumption	45 W	Salt Spray Test	ISO 9227 240H
Nominal Current at	24V=1.9A, 12V=3.8A	EMC	CISPR 25 Class 3, ISO 13766, ISO 14982, ISO 7637-2
Connector	Built-in Deutsch DT-2 (2-pin)	Operating Temperatures	-40°C... +85°C (Overheat protected)
Mount	Single Bolt M10	Part Numbers	High Beam: 984-305, Flood: 984-303, Wide Flood: 984-301, Low Beam: 984-304
Shock	60G		

CONNECTORS




Built-in Deutsch DT-2 (2-pin)

KEY FEATURES


- QUAKE dampening system
- Operational lumens output: 3000lm
- For extremely harsh conditions

LIGHT PATTERNS


**N4403 QD, N4404 3000lm
Wide Flood**




**N4403 QD, N4404 3000lm
Flood**




**N4403 QD, N4404 3000lm
High Beam**



**N4403 QD, N4404 3000lm
Low Beam**



**N4403 QD, N4404 2400lm
Diffused**



DRAWINGS

