



# MBI<sup>®</sup>



**REPARK**  
[www.REPARK.it](http://www.REPARK.it)

**RP**  
ROTATING PULVERIZER



## RP

### ROTATING PULVERIZER

The essential features for demolition jobs in a single tool. The RP is suitable for primary and secondary demolition, and it is available for 7 to 35 tons excavators.

- The **reinforced RP structure** is designed to last forever and facilitates the crushed material drop off increasing efficiency.
- The continuous **hydraulic rotation** enables accurate tool positioning in every working environment. In addition, the double-row thrust bearing ensures **high robustness and increases safety**.
- The **Speed-Valve** reduces opening and closing time boosting productivity.
- The **rod-cutting blades** are interchangeable and can be turned four times before replacement.



## TECHNICAL DATA

BT.RP.08

| MODEL                      |       | RP07           | RP16    | RP18    | RP25    |
|----------------------------|-------|----------------|---------|---------|---------|
| ROTATION                   |       | 360° Hydraulic |         |         |         |
| EXCAVATOR WEIGHT           | t     | 7-10           | 16-20   | 21-26   | 27-35   |
| TOOL WEIGHT*               | kg    | 660            | 1720    | 2000    | 2750    |
| OPENING                    | mm    | 500            | 700     | 760     | 930     |
| HEIGHT MAX.                | mm    | 1560           | 2020    | 2136    | 2440    |
| HYDRAULIC WORKING PRESSURE | bar   | 220-280        | 300-350 | 300-350 | 300-350 |
| OIL FLOW                   | l/min | 90-120         | 180-200 | 180-200 | 200-220 |

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.

\* Tool weight does include Mantovanibenne top bracket.

