

Adjustable arms series EVO Ø max 1/2" – up to 25 m length



Art. nos. 9090 – 9091 – 9092 – 9093

Automatic rewind, spring-driven hose reel, **adjustable arms series EVO**, in painted steel, suitable for hoses of max 25 m length and max diameter of 1/2". The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water. From the inlet swivel joint the fluid flows through an interchangeable hose connection adapter assembly on which the hose is mounted (standard version galvanized steel, available on demand also in stainless steel AISI 304 or AISI 316). Please see catalogue pages 228 and 229 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **/HB** to the article number (f. ex. 9090/HB)!



Art. nos. 9590 – 9591 – 9592 – 9593

Automatic rewind, spring-driven hose reel, **adjustable arms series EVO**, in stainless steel AISI 304, suitable for hoses of max 25 m length and max diameter of 1/2". The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water. From the inlet swivel joint the fluid flows through an interchangeable hose connection adapter assembly on which the hose is mounted (standard version stainless steel AISI 304, available on demand also in stainless steel AISI 316). Please see catalogue pages 228 and 229 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **/HB** to the article number (f. ex. 9590/HB)!



On demand these stainless steel hose reels can be supplied in accordance with directive ATEX 94/9/EC – group II – category 2.

Art. no.	Max working pressure	Connection threads IN - OUT	Internal Ø swivel joint	Max Ø hose	Max length hose 3/8" – 1/2"	Weight	Spool width	Suitable pivoting wall bracket	Included swivel joint	Dimensions (LxWxH) (mm)	
9090	600 bar	1/2" (M) – 1/2" (F)	10 mm	1/2"	15 m	12 kg	120 mm	9767	9951	240x550x450	
9091					20 m -15 m	13 kg		9767	9951		
9092					25 m -20 m	16 kg	150 mm	9768	9951		270x550x450
9093					25 m	19 kg	200 mm	9758	9951		310x550x450
9590	200 bar	1/2" (M) – 1/2" (F)	10 mm	1/2"	15 m	12 kg	120 mm	9760	9963	240x550x450	
9591					20 m -15 m	13 kg		9760	9963		
9592					25 m -20 m	16 kg	150 mm	9765	9963		270x550x450
9593					25 m	19 kg	200 mm	9775	9963		310x550x450



/HB Hydraulic spring brake kit

Safety device for the controlled rewind of hoses, installable on all spring-driven hose reel models, eliminating the dangers caused by an uncontrolled rewind or a sudden release of the hose when unwinded during its use.

