

Standard series **Ø max 1/2" - up to 20 m length**

Ø max 3/8" - up to 25 m length



Art. nos. **9016-9021-9022**

Art. nos. **9016-9021-9022**

Automatic rewind, spring-driven hose reel, standard series, in painted steel, suitable for hoses of max 20 m length (Ø hose 1/2") or max 25 m length (Ø hose 3/8"). The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water.

Please see catalogue pages 228 and 229 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9016/HB)!



Art. no. **9767**
Art. no. **9768**

Pivoting wall mounting bracket



Art. nos. **9517-9521-9522**

Art. nos. **9517-9521-9522**

Automatic rewind, spring-driven hose reel, standard series, in stainless steel AISI 304, suitable for hoses of max 20 m length (Ø hose 1/2") or max 25 m length (Ø hose 3/8").

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water at low and high pressure.

Please see catalogue pages 228 and 229 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9517/HB)!



Art. no. **9760**
Art. no. **9765**

Pivoting wall mounting bracket

(EX:) On demand these stainless steel hose reels can be supplied in accordance with directive ATEX 94/9/EC – group II – category 2.



Art. no.	Max working pressure	Connection threads IN - OUT	Internal Ø swivel joint	Max Ø hose	Max length hose	Weight	Spool width	Suitable pivoting wall bracket	Included swivel joint	Dimensions (LxWxH) (mm)
9016	600 bar	1/2" (M) – 1/2" (F)	10 mm	1/2"	15 m	13 kg	120 mm	9767	9951	250x570x450
9021				1/2"	20 m	18 kg	150 mm	9768	9951	260x570x450
9022				3/8"	25 m	19 kg	150 mm	9768	9951	260x570x450
9517	200 bar			1/2"	15 m	13 kg	120 mm	9760	9963	250x570x450
9521				3/8"	25 m	19 kg	150 mm	9765	9963	260x570x450
9522				1/2"	20 m	18 kg	150 mm	9765	9963	260x570x450



/HB Hydraulic spring brake kit

Safety device for the controlled rewind of hoses, installable on all spring-driven hose reel models, eliminating the dangers caused by an uncontrolled rewind or a sudden release of the hose when unwinded during its use.

